

**IN THE UNITED STATES PATENT AND TRADEMARK OFFICE**

In re Divisional Application of: )  
Tadahiro OHMI et al. ) Atty. Docket: SUGI0069  
Serial No. \_\_\_\_\_ (corresponding to )  
U. S. Patent Application Serial No. )  
09/117,350 filed July 28, 1998) )  
Filed: Herewith )  
For: METHOD FOR GENERATING )  
MOISTURE, REACTOR FOR )  
GENERATING MOISTURE, )  
METHOD FOR CONTROLLING )  
TEMPERATURE OF REACTOR )  
FOR GENERATING MOISTURE, ) Date: February 15, 2001  
etc. )

**PRELIMINARY AMENDMENT (A)**

**BOX: PATENT APPLICATION**  
Assistant Commissioner for Patents  
Washington, D. C. 20231

Sir:

Prior to calculating the filing fee, please amend the above-captioned application as follows:

**IN THE DRAWINGS:**

Please approve the changes to the drawings as indicated on the highlighted copies of the drawings filed herewith. These drawing corrections were requested in the parent application, i.e., Serial No. 09/117,350, of which this application is a divisional. Formal

renditions of those drawings with the noted changes made therein are being filed concurrently with this application.

**IN THE SPECIFICATION:**

Page 1, immediately below the title, please insert the following new paragraph:

-- This application is a divisional of U. S. Patent Application Serial No. 09/117,350, filed July 28, 1998, which corresponds to International Application No. PCT/JP97/00188, filed January 27, 1997. The entire disclosures of the above applications are hereby incorporated by reference. --

Page 2, line 14, change "SiO<sub>2</sub>" to --SiO<sub>2</sub>--.

Page 3, line 17, change "SiO<sub>2</sub>" to --SiO<sub>2</sub>--.

Page 16, line 8, change "2 m long" to --20 m long--.

Page 18, line 22, before "about 120°", insert --higher than--.

Page 38, line 11, change "5 mm" to --0.5 mm--.

Page 45, line 18, change "master" to --mass--.

Page 46, line 19, change "SiO<sub>2</sub>" to --SiO<sub>2</sub>--.

Page 47, line 7, change "SiO<sub>2</sub>" to --SiO<sub>2</sub>--.

Page 50, line 10, change "H<sub>2</sub> and O<sub>2</sub> with" to --H<sub>2</sub> and O<sub>2</sub> with--.

Page 57, line 23, change "SiO<sub>2</sub>" to --SiO<sub>2</sub>--.

**IN THE CLAIMS:**

For the convenience of the Examiner, all claims, as pending in this divisional application, whether or not these claims are now further amended, are reproduced herein.

Please cancel claims 5-8 and 11-14, without prejudice.

Please amend the claims as follows:

1. A process for generating water from hydrogen and oxygen in which hydrogen and oxygen are supplied into a reactor equipped with a material having catalytic action to activate a reactivity of hydrogen and/or oxygen and the reactor temperature is maintained below an ignition temperature of hydrogen and gas containing hydrogen to allow hydrogen and oxygen to react and generate water while preventing combustion of hydrogen and oxygen.

2. **(Amended)** The process for generating water of claim 1, wherein hydrogen and oxygen are allowed to react while temperature at a vicinity of a hydrogen and oxygen inlet end of the reactor is held to 200°C to 500°C and temperature in a vicinity of a water outlet end of the reactor is held to about 600°C or lower.

3. **(Amended)** The process for generating water of claim 1, wherein a supply ratio of a volume of hydrogen gas to that of oxygen is set to 1[:]to not less than 0.5 or 1[:]to not higher than 0.5.

4. **(Amended)** The process for generating water of claim 1, **[claim 2, or claim 3]** wherein the water generated in the vicinity of an outlet end of the reactor is diluted and gas containing water of an optional concentration is guided out.

5. **(Cancelled)** A water-generating reactor in which cylinders made of a material having catalytic action that can activate a reactivity of hydrogen and/or oxygen or a material whose surface is covered with the material having the said catalytic action are placed in a casing to form passages through which hydrogen and oxygen flows while making contact with inner wall surfaces and/or outer wall surfaces of the cylinders, and a heater is placed outside or inside of the casing.

6. **(Cancelled)** The water-generating reactor of claim 5 wherein hydrogen and oxygen are introduced into the inside of at least one of the cylinders and guided therein to flow towards the outlet end, then guided outside the cylinder to return to flow towards the inlet end, and is thereafter introduced into the inside of another cylinder from the inlet end and guided therein to flow towards the outlet end.

7. **(Cancelled)** The water-generating reactor of claim 5 or claim 6 wherein the cylinder is a pipe made of nickel.

8. **(Cancelled)** The water-generating reactor of claim 5 wherein the cylinder comprises nickel, stainless steel, and Hastelloy cylinder portions connected in series, or nickel and stainless steel cylinder portions connected in series, with the nickel portion located at a water outlet end of the reactor.

9. A water-generating reactor in which columns filled with granules made of a material having catalytic action that can activate reactivity of hydrogen and/or oxygen:

sintered material of powders or fibers made of the material having the catalytic action;

laminates or honeycomb bodies comprising thin sheets made of the material having the catalytic action;

mesh bodies, sponge bodies, or fin-shaped bodies made of the material having the catalytic activity;

or granules sintered materials, thin sheet laminates, honeycomb bodies, mesh bodies, sponges or fin-shaped bodies whose surfaces are covered with the material having the catalytic activity are placed or two or more of these are placed in a casing, and passages are formed for allowing hydrogen and oxygen to flow therethrough while coming in contact with

said granules, sintered materials, laminates, honeycomb bodies, mesh bodies, or fin-shaped bodies, and at the same time, a heater being placed outside or inside the casing.

10. **(Amended)** The water-generating reactor of claim 9, wherein the material having catalytic action is nickel.

11. **(Cancelled)** The water-generating reactor of claim 5 or claim 9 wherein a hydrogen and oxygen preheating portion is installed at a portion for introducing hydrogen and oxygen into the casing.

12. **(Cancelled)** The water-generating reactor of claim 5 or claim 9 wherein a whole or part of a surface of the catalyst material in the reactor or a whole surface in contact with gas of the casing, including forward and backward piping systems, is mirror-surfaced-finished.

13. **(Cancelled)** The water-generating reactor of claim 5 or claim 9 wherein a whole or part of the casing, including the forward and backward piping system of the reactor, is made of heat-resistant metal or corrosion-resistant metal.

14. **(Cancelled)** The water-generating reactor of claim 5 or claim 9 wherein a whole or part of the surface of the casing in contact with gas, including the forward and backward piping system, is covered with oxidation-resistant, reduction-resistant, or corrosion-resistant protection film, or is provided with surface-treatment having a performance equivalent to that of the protection film.

15. A water-generating reactor comprising a metal reactor body provided with an inlet and a water and moisture gas outlet and a platinum coating film provided on an inner wall surface of the reactor body, wherein hydrogen and oxygen supplied from the inlet are

brought in contact with the platinum coated film to activate a reactivity and water is generated from the hydrogen and the oxygen.

16. A water-generating reactor comprising a reactor body of heat-resistant material and having an inlet and a water and moisture gas outlet, a gas diffusing member in an internal space of the reactor body, and a platinum coating film on an inner wall surface of the reactor body wherein hydrogen and oxygen supplied from the inlet and diffused by the gas diffusing member are brought into contact with the platinum coating film to activate a reactivity, and water is thereby generated from the hydrogen and oxygen.

17. (Amended) The water-generating reactor of claim 15, [or claim 16] wherein the reactor body is made from heat-resistant metal, and the platinum coating film is 10Å to 0.5 mm thick and is formed by one of a plating method, a sputtering method, a vapor deposition method, a cladding method, an ion plating method and a hot press method.

18. (Amended) The water-generating reactor of claim 15, [or claim 16] wherein the reactor body is made from heat-resistant metal, and the platinum coated film is a film 10Å to 0.5 mm thick formed on a barrier film of a non-metal material on the inner wall surface of the reactor body by one of a plating method, a sputtering method, a vapor deposition method, a cladding method, an ion plating method, or a hot press method.

19. (Amended) The water-generating reactor of claim 15, [or claim 16] wherein the gas supplied to the reactor body is an oxygen rich gas whose ratio of oxygen to hydrogen  $H_2/O_2$  is  $H_2/O_2 < 1/2$  or a hydrogen rich gas whose ratio of oxygen is hydrogen  $H_2/O_2$  is  $H_2/O_2 > 1/2$ .

20. **(Amended)** The water-generating reactor of claim 16, wherein the gas diffusing member comprises a reflector plate located opposite the inlet and a filter located downstream of the reflector plate or a reflector plate located opposite the inlet, a filter located downstream of the reflector plate, and a reflector plate located opposite the water and moisture gas outlet.

21. **(Amended)** The water-generating reactor of claim 16, wherein the gas diffusing member comprises a cylinder, cone, or disk made of a filter placed opposite the inlet.

22. **(Amended)** The water-generating reactor of claim 16, wherein the gas diffusing member comprises a disk placed opposite the inlet and having a filter at a periphery portion.

23. **(Amended)** The water-generating reactor of claim 18, wherein the barrier film is made of at least one of TiN, TiC, TiCN, or TiAlN.

24. A process for controlling temperature of a water-generating reactor which has a catalyst in a casing that can activate reactivity of hydrogen or oxygen and in which hydrogen and oxygen are allowed to react with each other to generate water at high temperatures, wherein an upstream-end temperature of hydrogen and oxygen under reaction in the said water-generating reactor is held lower than that of a downstream-end temperature.

25. The process for controlling temperature of the water-generating reactor of claim 24 wherein the upstream-end temperature of hydrogen and oxygen under reaction is held in a range of from 200°C to 500°C and the downstream-end temperature is held at about 600°C or lower.

26. **(Amended)** A process for controlling temperature of a water-generating reactor which has a catalyst in a casing that can activate a reactivity of hydrogen or oxygen and in which hydrogen and oxygen are allowed to react at high temperatures to generate water,

wherein areas of contact between the catalyst in the casing and a mixture gas are smaller on upstream-end reacting gases than on a downstream-end reacting gases to reduce reaction amounts of oxygen and hydrogen so that a temperature rise at the upstream-end reacting gas is prevented.[.]

27. A process for controlling temperature of a water-generating reactor which has a catalyst in a casing that can activate reactivity of hydrogen and/or oxygen and in which hydrogen and oxygen are allowed to react at high temperatures to generate water, wherein a catalytic action of the catalyst in the casing is designed to be smaller on upstream-end reacting gases than on a downstream-end reacting gases to reduce reaction amounts of oxygen and hydrogen so that a temperature rise on the upstream-end reaction gases in the casing is prevented.

28. **(Amended)** A process for controlling temperature of a water-generating reactor which has a catalyst in a casing that can activate reactivity of hydrogen and/or oxygen and in which hydrogen and oxygen are allowed to react at high temperatures to generate water, wherein positions for supplying gases to come in contact with the catalyst in the casing are scattered to reduce reaction amounts of oxygen and hydrogen at the upstream end so that temperature rises of upstream end reacting gas in the casing is prevented.

29. A process for forming a platinum coated catalyst layer in a water-generating reactor in which a platinum coated film formed on an inner wall surface of a metal reactor body having an inlet as well as a water and moisture gas outlet serves as a catalyst for activating a reactivity of hydrogen and oxygen supplied from the inlet, with the oxygen and hydrogen being brought into contact with the platinum coating film to generate water from the



hydrogen and oxygen in the reactor, wherein the inner wall surface of the said metal reactor body is surface-treated by cleaning, then a barrier film of nonmetallic material of oxides or nitrides is formed on the inner wall surface of the reactor body, and thereafter the platinum coated film is formed on the barrier film.

30. **(Amended)** The process for forming the platinum coated catalyst layer in the water-generating reactor of claim 29, wherein the barrier film is made of one of TiN, TiC, TiCN, TiAlN, Al<sub>2</sub>O<sub>3</sub>, Cr<sub>2</sub>O<sub>3</sub>, [SiO<sub>2</sub>] SiO<sub>2</sub>, and CrN.

31. **(Amended)** The process for forming the platinum coated catalyst layer in the water-generating reactor of claim 29, wherein the reactor body is made of stainless steel and the barrier film is a film made of TiN.

32. **(Amended)** The process for forming the platinum coated catalyst layer in the water-generating reactor of claim 29, [claim 30, or claim 31] wherein the thickness of the barrier film is 0.1 – 5 μm and the barrier film is formed by an ion plating method or a sputtering method.

33. **(Amended)** The process for forming the platinum coated catalyst layer in the water-generating reactor of claim 29, [claim 30, claim 31 or claim 32] wherein the thickness of the platinum coated film is 0.1 – 3 μm and at the same time the platinum coated film is formed by an ion plating method or a sputtering method.

Please add the following new claims:

-- 34. The process for generating water of claim 2, wherein the water generated in the vicinity of an outlet end of the reactor is diluted and gas containing water of an optional concentration is guided out.

35. The process for generating water of claim 3, wherein the water generated in the vicinity of an outlet end of the reactor is diluted and gas containing water of an optional concentration is guided out.

36. The water-generating reactor of claim 16, wherein the reactor body is made from heat-resistant metal, and the platinum coating film is 10Å to 0.5 mm thick and is formed by one of a plating method, a sputtering method, a vapor deposition method, a cladding method, an ion plating method and a hot press method.

37. The water-generating reactor of claim 16, wherein the reactor body is made from heat-resistant metal, and the platinum coated film is a film 10Å to 0.5 mm thick formed on a barrier film of a non-metal material on the inner wall surface of the reactor body by one of a plating method, a sputtering method, a vapor deposition method, a cladding method, an ion plating method, or a hot press method.

38. The water-generating reactor of claim 16, wherein the gas supplied to the reactor body is an oxygen rich gas whose ratio of oxygen to hydrogen  $H_2/O_2$  is  $H_2/O_2 < 1/2$  or a hydrogen rich gas whose ratio of oxygen is hydrogen  $H_2/O_2$  is  $H_2/O_2 > 1/2$ .

39. The water-generating reactor of claim 37, wherein the barrier film is made of at least one of TiN, TiC, TiCN, or TiAlN.

40. The process for forming the platinum coated catalyst layer in the water-generating reactor of claim 30, wherein the thickness of the barrier film is 0.1 – 5 μm and the barrier film is formed by an ion plating method or a sputtering method.

41. The process for forming the platinum coated catalyst layer in the water-generating reactor of claim 31, wherein the thickness of the barrier film is  $0.1 - 5 \mu\text{m}$  and the barrier film is formed by an ion plating method or a sputtering method.

42. The process for forming the platinum coated catalyst layer in the water-generating reactor of claim 30, wherein the thickness of the platinum coated film is  $0.1 - 3 \mu\text{m}$  and at the same time the platinum coated film is formed by an ion plating method or a sputtering method.

43. The process for forming the platinum coated catalyst layer in the water-generating reactor of claim 31, wherein the thickness of the platinum coated film is  $0.1 - 3 \mu\text{m}$  and at the same time the platinum coated film is formed by an ion plating method or a sputtering method.

44. The process for forming the platinum coated catalyst layer in the water-generating reactor of claim 32, wherein the thickness of the platinum coated film is  $0.1 - 3 \mu\text{m}$  and at the same time the platinum coated film is formed by an ion plating method or a sputtering method.

45. The process for forming the platinum coated catalyst layer in the water-generating reactor of claim 40, wherein the thickness of the platinum coated film is  $0.1 - 3 \mu\text{m}$  and at the same time the platinum coated film is formed by an ion plating method or a sputtering method.

46. The process for forming the platinum coated catalyst layer in the water-generating reactor of claim 41, wherein the thickness of the platinum coated film is  $0.1 - 3 \mu\text{m}$

µm and at the same time the platinum coated film is formed by an ion plating method or a sputtering method. --

### REMARKS

When filing the parent application, i.e., Serial No. 09/117,350, on July 28, 1998, proposed corrected drawings were filed in order to make the drawings consistent with the U. S. Rules, e.g., to identify the drawings as "Fig. 1", "Fig. 2", etc., and to use Roman numerals to identify cross-sections, as well as the ensure that the drawings were consistent with the translated specification. Although a Form PTO-948 - Notice of Draftsperson's Patent Drawing Review was issued in the parent application on August 23, 1999, the proposed drawing corrections were not addressed by the Examiner during prosecution of the parent application. Accordingly, the proposed drawing corrections are again submitted with the present divisional application. Additionally, a complete set of formal drawings, i.e., containing Figs. 1-53, making the proposed drawing corrections and addressing the objections of the Draftsperson, as stated in the Form PTO-948 issued in the parent application, are filed concurrently herewith. It is respectfully requested that the Examiner and Draftsperson approve the new set of formal drawings.

The specification has been amended to correct idiomatic, grammatical or typographical errors in the original PCT application. No new matter has been added.

Claims 5-8 and 11-14, i.e., the claims being prosecuted in the parent application, are cancelled.

The claims have been amended to delete multiple dependencies, thus reducing the filing fee. Additionally, new claims 34-46 have been added. Claims 34 and 35 go to the subject matter of claim 4, but depend respectively on claims 2 and 3. Claims 36-38 go to the subject matter of claims 17-19, respectively, but depend on claim 16. Claim 39 goes to the subject matter of claim 23 but depends on claim 37. Claims 40-41 go to the subject matter of claim 32 but depend respectively on claims 30 and 31. Claims 42-46 go to the subject matter of claim 33 but depend respectively on claims 30-32, 40 and 41.


Accordingly, claims 1-4, 9-10, and 15-46 are presented in this divisional application for examination.

In view of the above, it is believed that this application is in good condition for examination, and the Examiner's early and favorable action is respectfully solicited.

Questions are welcomed by the below-signed attorney for applicants.

Respectfully submitted,

GRIFFIN & SZIPL, PC

  
\_\_\_\_\_  
Joerg-Uwe Szimpl  
Reg. No. 31,799

GRIFFIN & SZIPL, PC  
Suite PH-1  
2300 Ninth Street, South  
Arlington, VA 22204

Telephone: (703) 979-5700  
Facsimile: (703) 979-7429  
Customer No.: 24203

Fig. 1




Fig. 2








Fig. 3





Fig. 4  
~~4~~



~~5~~

Fig. 5






Fig. 6




Fig. 7




Fig. 8





Fig. 9,  
~~Fig. 9~~



~~Fig. 10~~ Fig. 10




Fig. 11

~~Fig. 11~~





Fig. 12  
~~12~~



~~13~~  
 Fig. 13






Fig.14  
14

Fig. 15

~~Fig. 15~~

$H_2 : O_2 = 67\% : 33\%$ , 25scc/min



~~Fig. 16~~ Fig. 16

$H_2 : O_2 = 20\% : 10\%$ , 75scc/min







Fig. 17  
~~Fig. 17~~ $H_2 : O_2 = 75\% : 25\%$ , 25scc/min~~Fig. 18~~ Fig. 18 $H_2 : O_2 = 30\% : 10\%$ , 25scc/min

Fig. 19

~~Fig. 19~~

Ni Tube ( 1/4 inch x 2m ) , 500°C


H<sub>2</sub> : O<sub>2</sub> = 67% : 33%



~~Fig. 20~~ Fig. 20


Ni Filter

H<sub>2</sub> : O<sub>2</sub> = 67% : 33%, 25scc/min



21

Fig. 2/





~~Fig. 22~~  
Fig. 22

Ni Ribbon (t 0.3 x 20 x 1000mm)

H<sub>2</sub> : O<sub>2</sub> = 67% : 33%, 25scc/min




Fig. 23  
~~Fig. 23~~

Ni Ribbon ( $t = 0.3 \times 20 \times 1000\text{mm}$ ),  $500^\circ\text{C}$   
 $\text{H}_2 : \text{O}_2 = 67\% : 33\%$




~~Fig. 24~~ Fig. 24

Fig. 25  
~~Fig. 25~~



~~Fig. 26~~ Fig. 26




Fig. 27  
~~Fig. 27~~




Fig. 28

~~28~~




Fig. 29



~~Fig. 29~~~~Fig. 30~~ Fig. 30

Fig. 3)  
~~Fig. 3~~

H<sub>2</sub>: 100scc/min  
O<sub>2</sub>: 33scc/min  
620°C

H<sub>2</sub>: O<sub>2</sub> = 3 : 1




Fig. 32

~~Fig. 32~~

H<sub>2</sub> : O<sub>2</sub> = 4 : 3







Fig. 33  
~~Fig. 33~~



~~Fig. 34~~  
Fig. 34






Fig. 35  
~~35~~




~~36~~ Fig. 36



~~37~~ Fig. 37



Fig. 38  
~~38~~



~~39~~ Fig. 39




Fig. 40




Fig. 41  
~~41~~






Fig. 42



~~Fig. 43~~

Fig. 43



~~Fig. 44~~

Fig. 44






Fig. 45





Fig. 46  
~~Fig. 46~~



2 8 / 2 5

03400 630360


88 06/04 180 15.25 FAX 06 201 5508

1711 1 14 1017274E


777 05/ 7717

087

~~Fig. 47~~  
Fig. 47



~~Fig. 48~~  
Fig. 48



~~Fig. 49~~

Fig. 49




Fig. 50

~~Fig. 50~~




Fig. 51  
~~Fig. 51~~




Fig. 52


~~Fig. 52~~

Fig. 53

~~Fig. 53~~